

**SAIBM-M8-3P-(IF)****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female sockets for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M8 round plug-in connectors are particularly suited to applications where space is limited.

The screw connection can be used in a wide range of applications. With this technology the conductor, optionally with wire-end ferrules, can be plugged into connection elements and secured with a screw. It is the classic, cheapest form of connection technology that also supports multi-conductor connections.

**General ordering data**

Type	SAIBM-M8-3P-(IF)
Order No.	<a href="#">1010080000</a>
Version	Sockets prefabricated to customer spec., Plugs prefabricated to customer spec., M8, Female socket, straight
GTIN (EAN)	4032248715305
Qty.	1 pc(s).

## SAIBM-M8-3P-(IF)

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technische Daten

### Dimensions and weights

Net weight 20 g

### Technical data customisable plug-in connectors

Cable diameter	3.5...5 mm	Cable diameter, max.	5 mm
Cable diameter, min.	3.5 mm	Coding	none
Connection cross-section, max.	0.5 mm <sup>2</sup>	Connection cross-section, min.	0.14 mm <sup>2</sup>
Contact surface	Gold-plated	Housing main material	CuZn
Insulation resistance	10 <sup>8</sup> Ω	No. of poles	3
Plugging cycles	≥ 100	Pollution severity	3
Protection degree	IP 67	Rated current	4 A
Rated voltage	60 V	Rated voltage (text)	60 V (3-pole) / 30 V (4-pole)
Shield connection	Yes	Threaded ring material	Diecast zinc
Type of connection	Screw connection		

### Classifications

ETIM 3.0	EC002062	UNSPSC	30-21-18-01
eClass 5.1	27-26-07-01	eClass 6.2	27-26-07-02
eClass 7.1	27-44-01-02		

### Approvals

Approvals	
ROHS	Conform